

## 50 044 Universal varnish, satin-matt

### product name:

- Universal varnish, satin-matt.

### contains:

- Acrylic resin, mineral spirit, matting agent.

### basic information:

- Final varnish for several painting techniques (e.g. oil or acrylic) based on a high-quality synthetic resin.

### characteristics:

- Satin-matt
- colourless and elastic
- non-yellowing and age-resistant
- fast drying.

### handling:

- Shake well before use.
- The product is ready to use, but can be diluted with e.g. *turpentine substitute 50019*.
- May only be applied with a suitable varnish brush at room temperature to the layer of paint after it has dried completely (drying time for oil colours: at least 8 – 12 month; drying time for thin acrylic colours: approx. 3 days, for thicker acrylic layers: approx. 1 – 2 weeks; drying time for gouache: approx. 1 day).
- Please clean tools as soon as possible with e.g. *turpentine substitute 50019* or *brush cleaner 50051 / 50052*.
- The dried varnish layer remains soluble in *turpentine substitute 50019* or *varnish remover 50060* over a long period.
- The varnish coats normally used in practice give no special UV protection to the paints used. For this reason, we recommend that you use high-quality and lightfast artists' paints from the outset as far as possible.
- The subsequent varnishing of the surface of a picture produced using materials low in binding agents, especially pastels, gouache and water-colours, may cause the colour shade to become significantly darker. Varnishes also may increase transparency of some grounds, like e.g. papers.
- Close immediately after use.
- Store in a cool and dry place.
- Individual pre-tests are required (see footer).

### product labeling:

- Please refer to the individual safety data sheet on our website [www.schmincke.de](http://www.schmincke.de).

DrK/01.07.2014

H. Schmincke & Co. GmbH & Co. KG · Otto-Hahn-Str. 2 · D - 40699 Erkrath ·  
Tel.: +49-211-2509-0 · [www.schmincke.de](http://www.schmincke.de) · [info@schmincke.de](mailto:info@schmincke.de)



The described product characteristics and example applications have been tested at the Schmincke laboratory. The information is based on the technical knowledge and experience which are presently available to us. In view of the diversity of applications with regard to painting techniques, materials and working conditions and the numerous possible influencing factors, the information refers to general areas of application. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application; use of the products is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept any liability for damage arising in connection with the use of our products.